



# MAD Elevator Inc. – Position Indicator Survey

Date: \_\_\_\_\_

Job/Building Name: \_\_\_\_\_

Contact Name: \_\_\_\_\_

City/State: \_\_\_\_\_

Company Name: \_\_\_\_\_

P.O. # \_\_\_\_\_

Contact # \_\_\_\_\_

## SIGNAL FORMAT

- Line per floor
- Binary
- Units and tens
- Gray code
- Inverted binary
- Micro Comm (3 wire)

## SIGNAL VOLTAGE DIRECT

- 6-20 VDC Positive signal, negative common
- 24-48 VDC Positive signal, negative common
- 125 VDC Positive signal, negative common
- 6-20 VDC Negative signal, positive common
- 24-48 VDC Negative signal, positive common
- 125 VDC Negative signal, positive common

## CAN TYPE

- EC CAN
- GAL CAN
- TK CAN
- JRT CAN
- DEUM Binary
- DEUM Line/Floor
- Gray Code
- Smartrise Serial
- OTIS Serial
- Multi-Parallel Input

## ALTERNATE

- 24 VAC
- 48 VAC
- 125 VAC

## FLOOR MARKINGS

Notes

Other (Specify): \_\_\_\_\_

SIGNED: \_\_\_\_\_

PER: \_\_\_\_\_

Please send completed survey to your MAD Sales representative, or to sales@madelevator.com